ARL90-hybrid TECHNICAL DATA SHEET (airless/airspray road marking machine)

Dimensions: 190x80x h105 cm; Weight: 513 Kg



Photo doesn't show standard machine.

Gasoline engine:

- -power 23 HP
- -electric starting

Light and turning light

Hydraulic drive with:

- -2 motors directly coupled on rear wheels
- -control for forward, reverse and neutral gear
- -<u>VARIABLE-FLOW PUMP</u>: guarantees more **safety** for operator and better **performance**. Allows to overcome steep slopes

Swivel front wheel. It can be locked or unlocked during the work by a pneumatic control on dashboard

Trailer with standing driver

Machine is equipped with all safety devices according to EU requirements. Machine conforms to:

- EU Directive 2006/42/EC on Machinery
- EU Directive 14/68/EU for Pressure Equipment (PED directive)

Pressurized paint tank:

- -capacity 90 l
- -made of stainless steel
- -with manual stirrer and cover totally removable for easier and quicker cleaning

Solvent tank for flushing of gun and paint hose

Airless hydraulic piston pump:

-max. vol. flow 8,9 l/min

Piston pulsation dampener

Compressor:

-flow air rate 827 l/min

Dual-technology paint outlet group:

- airless paint aspiration
- airspray paint delivery

Airless automatic paint gun mounted on fixed L support (with adjustable height). Standard nozzle for 10-20 cm line. (*Line width can be ranged from 10 cm to 30 cm by changing nozzle and adjusting gun height. Fixed support can be replaced with pneumatic support. Look at optional)*

High-pressure paint filter

MAX. LINE WIDTH: 90 cm

(achievable only with proper optional equipment)

Electronic controller and spacing device C9000:

- 10 programs storable
- display of effective applied thickness (average every 250 m), with alarm when the speed of application is not compatible with thickness set
- data recorded for each gun: applied thickness in micron; total working hours; total driven metres; total solid line metres; total empty space metres; total sprayed paint
- data recorded for each pump: total number of pump cycles
- total data recorded for machine: total working hours, total driven metres; total driven Km; total sprayed paint; total hours and pump cycles
- daily report, downloadable with USB stick. Storable capacity7 days. Thickness applied each minute (with date and time)



SPRAYABLE PRODUCTS:

for airless: not refractive paints, specifically formulated for airless application

for airspray: refractive paints, not refractive paints, special paints with antiskid



OPTIONAL EQUIPMENT:

- Second airless automatic paint gun with independent control to stripe 50 cm or 2 lines at the same time (for example continuous line + skip line)
- Third airless automatic paint gun to stripe 90 cm
- Pneumatic support for paint gun (one disc), to keep automatic gun always at the same distance from ground, ensuring constant width of the line. (SUGGESTED OPTIONAL)
- Airless manual paint gun-short with 10 m hose, for stenciling. (SUGGESTED OPTIONAL)
- Airless manual paint gun -long (with extension 45 cm) with 10 m hose, for stenciling without bending and standing farther from paint spray
- Pressurized glass bead system (SUGGESTED OPTIONAL) consisting of:
 - glass bead tank. Available capacity: pressurized conic tank capacity 20 I
 - pressurized conic tank capacity 38,5 l
 - automatic glass bead gun with adjustable diffuser
 - closing delay regulator for bead gun
- Second automatic glass bead gun with independent delay regulator.

Attention: it can be used only if striper is equipped with optional pressurized Glass bead system

- Third automatic glass bead gun.

Attention: it can be used only if striper is equipped with optional pressurized Glass bead system

- Manual glass bead gun with air hose and bead hose, for bead application on stenciling.

 Attention: it can be used only if striper is equipped with optional pressurized Glass bead system
- Supplementary tank for paint. Available capacities: pressurized paint tank capacity 15,5 I (airspray)
 - pressurized paint tank capacity 26 I (airspray)
 - gravity paint tank capacity 50 I (airless)
- Airspray automatic paint gun with line limiter (shroud), mounted on fixed support with gun height adjustable. Standard nozzle for 10-20 cm line
- Airspray manual paint gun with 7 m air hose and 7 m paint hose, for stenciling. Low pressure.





