CPm2 TECHNICAL DATA SHEET (sprayer for cold paint –airspray or for glass beads and antiskid)

Dimensions: 140x65x h130 cm; Weight (standard machine without paint tank): 75 kg



Gasoline engine:

- -power 6 HP
- -self-winding pull start

Compressor:

-flow air rate 394 l/min

Air tank

SPRAYABLE PRODUCTS: refractive paints, not refractive paints, special paints with antiskid. Glass beads and antiskid

Photo doesn't show standard machine.

The sprayer can be equipped with:

- paint tank and manual paint gun for APPLICATION ON SURFACES OF COLD PAINT-AIRSPRAY
 or with
- glass bead tank and manual glass bead gun for APPLICATION ON SURFACES OF GLASS BEADS AND ANTISKID.

OPTIONAL EQUIPMENT:

- Pressurized paint tank capacity 15,5 I
- Pressurized paint tank in INOX capacity 15,5 l
- Pressurized paint tank capacity 26 I
- Solvent tank for flushing of gun and paint hose (capacity 2,5 l)
- Manual paint gun-short with 5 m air hose and 5 m paint hose, for stenciling (crosswalk, symbols, legends, stops, ...)
- Manual paint gun long (with extension 40 cm) with 5 m air hose and 5 m paint hose, for stenciling without bending and standing farther from paint spray
- Pressurized conic tank for glass beads capacity 20 I
- Pressurized conic tank for glass beads capacity 38,5 I
- Manual glass bead gun with air hose and bead hose, for bead application on stenciling.

Machine conforms to:

EU Directive 2006/42/EC on Machinery

► EU Directive 14/68/EU for Pressure Equipment (PED directive)





CPm2 TECHNICAL DATA SHEET on May 25th 2018. CMC reserves the right to make changes at any time, without notice.

Macchine Traccialinee Marking Machines