## L250SN TECHNICAL DATA SHEET (airspray road marking machine)

Dimensions: 345x110x h without warning board 210 cm; Weight: 1300 Kg



Photo doesn't show standard machine.

**TURBO diesel engine:** -power 44 HP -liquid cooling

Lights and turning light

Warning board with arrow for left/right car overtaking and 2 flashing

Hydraulic drive with:

- 2 motors directly coupled on rear wheels

-hydraulic negative brakes

-control for forward, reverse and neutral gear with engagement of negative brakes

-variable-flow pump

**Central steering**. <u>Central steering allows to easily stripe sharper curves</u> <u>and makes L250SN optimal to stripe U-bend roads</u>

Steering diameter 6,5 m

Seat with adjustable position (left/right; forward/back)

Machine is equipped with all safety devices according to EU requirements. Machine conforms to:

- EU Directive 2006/42/EC on Machinery
- EU Directive 14/68/EU for Pressure Equipment (PED directive)

## Pressurized paint tank: -capacity 250 l -made of stainless steel -with hydraulic stirrer

Solvent tank for flushing of gun and paint hose

**Pressurized glass bead tank**, capacity 100 l. With regulator of pressure and moisture separator

**Compressor:** -flow air rate 1390 l/min

Automatic paint gun with line limiter (shroud), mounted on fixed support with gun height adjustable. (*Fixed support can be replaced with pneumatic support or with marking discs. Look at optional*). Standard nozzle for 10-20 cm line

Automatic glass bead gun. Diffuser with adjustable slope and adjustable opening angles. Closing delay regulator for bead gun

**MAX. LINE WIDTH:** 90 cm (achievable only with proper optional equipment)

## Electronic spacing device C8000:

- 8 programs storable
- control: upto 3 guns with only one program
- alarm when speed is outside the range of minimum/maximum speed set
- data recorded for each gun: total solid line metres
- total data recorded for machine: total driven Km





## **OPTIONAL EQUIPMENT:**

- Trailer for cones with seat for operator (SUGGESTED OPTIONAL)

- Second automatic paint gun with independent control to stripe 50 cm or 2 lines at the same time (for example continuous line + skip line) (SUGGESTED OPTIONAL)

- Third automatic paint gun to stripe 90 cm

- **Pneumatic support for the paint gun (one disc),** to keep automatic gun always at the same distance from ground, ensuring constant width of the line (SUGGESTED OPTIONAL)

- Marking discs, to get a perfect definition of line edges. Useful particularly for concrete surfaces. Available in following widths: - marking discs for 10-20 cm line

- marking discs for 10-30 cm line

- marking discs for 50 cm line. <u>Attention</u>: 50 cm marking discs can be used only if striper is equipped with optional second automatic paint gun

- marking discs for 90 cm line. <u>Attention</u>: 90 cm marking discs can be used only if striper is equipped with optional third automatic paint gun

- Manual paint gun-short with 7 m air hose and 7 m paint hose, for stenciling

- Manual paint gun - long (with extension 40 cm) with 7 m air hose and 7 m paint hose, for stenciling without bending and standing farther from paint spray

- Second automatic glass bead gun with independent delay regulator (SUGGESTED OPTIONAL)

- Third automatic glass bead gun

- Manual glass bead gun with air hose and bead hose, for bead application on stenciling


- Supplementary pressurized tank for paint capacity 26 I

- 26 I pressurized tank and side extension bracket for pre-marking









Automatic paint gun Automatic glass bead gun Second automatic paint gun (optional) Second automatic glass bead gun (optional)

Marking discs (optional)

