

L50ITP-EVO - L50ITPEVO-H TECHNICAL DATA SHEET (airspray road marking

machine)

Dimensions: 175x70x h105 cm; Weight: 250 Kg



Photo doesn't show standard machine.

Gasoline engine:

-power 9,5 HP (L50ITP-EVO) - 8,5 HP engine HONDA GX270 (L50ITPEVO-H)

-electric starting

Hydraulic drive with:

-2 motors directly coupled on rear wheels

-control for forward, **reverse** and neutral gear

-**VARIABLE-FLOW PUMP**: guarantees more **safety** for operator and better **performance**. Allows to overcome steep slopes

Swivel front wheel. It can be locked or unlocked during the work by a pneumatic control on dashboard

Pressurized paint tank:

-capacity 50 l

-with manual stirrer and cover totally removable for easier and quicker cleaning

Solvent tank for flushing of gun and paint hose

Compressor:

-flow air rate 515 l/min

Automatic paint gun with line limiter (shroud), mounted on fixed support with gun height adjustable. (Fixed support can be replaced with pneumatic support or with marking discs. Look at optional). Standard nozzle for 10-20 cm line

MAX. LINE WIDTH: 30 cm

(achievable only with proper optional equipment)



SPRAYABLE PRODUCTS: refractive paints, not refractive paints, special paints with antiskid

Machine is equipped with all safety devices according to EU requirements.

Machine conforms to:

- *EU Directive 2006/42/EC on Machinery*
- *EU Directive 14/68/EU for Pressure Equipment (PED directive)*

OPTIONAL EQUIPMENT:

- **Light**, for night works

- **Turning light**, for a better visibility of operator on the street. **(SUGGESTED OPTIONAL)**

Electronic spacing device C8000:

- 8 programs storable
- control: upto 3 guns with only one program
- alarm when speed is outside the range of minimum/maximum speed set
- data recorded for each gun: total solid line metres
- total data recorded for machine: total driven Km

- **Trailer with standing driver (SUGGESTED OPTIONAL)**

- **Pneumatic support for paint gun (one disc)**, to keep automatic gun always at the same distance from ground, ensuring constant width of the line **(SUGGESTED OPTIONAL)**

- **Marking discs**, to get a perfect definition of line edges. Useful particularly for concrete surfaces. Available in following widths:

- marking discs for 10-20 cm line
- marking discs for 10-30 cm line

- **Manual paint gun-short with 5 m air hose and 5 m paint hose**, for stenciling **(SUGGESTED OPTIONAL)**

- **Manual paint gun - long (with extension 40 cm) with 5 m air hose and 5 m paint hose**, for stenciling without bending and standing farther from paint spray

- **Pressurized glass bead system** consisting of:

- **pressurized glass bead tank capacity 15,5 l**
- automatic glass bead gun with adjustable diffuser
- closing delay regulator for bead gun

- **Manual glass bead gun with air hose and bead hose**, for bead application on stenciling.

Attention: it can be used only if striper is equipped with optional pressurized Glass bead system

- **Supplementary pressurized tank for paint**. Available capacities: - **pressurized paint tank capacity 15,5 l**
- **pressurized paint tank capacity 26 l**



