L90IETP TECHNICAL DATA SHEET (airspray road marking machine)

Dimensions: 190x80x h105 cm; Weight: 415 Kg



Photo doesn't show standard machine.

Gasoline engine: -power 21 HP -electric starting

Light and turning light

Hydraulic drive with:

-2 motors directly coupled on rear wheels
-control for forward, reverse and neutral gear
-VARIABLE-FLOW PUMP: guarantees more safety for operator and better performance. Allows to overcome steep slopes

Swivel front wheel. It can be locked or unlocked during the work by a pneumatic control on dashboard

Trailer with standing driver

Machine is equipped with all safety devices according to EU requirements. Machine conforms to:

- EU Directive 2006/42/EC on Machinery
- EU Directive 14/68/EU for Pressure Equipment (PED directive)

Pressurized paint tank:

-capacity 90 I -made of <u>stainless steel</u> -with manual stirrer and cover totally removable for easier and quicker cleaning

Solvent tank for flushing of gun and paint hose

Compressor: -flow air rate 827 l/min

Automatic paint gun with line limiter (shroud), mounted on fixed support with gun height adjustable. (*Fixed support can be replaced with pneumatic support or with marking discs. Look at optional*). Standard nozzle for 10-20 cm line

MAX. LINE WIDTH: 50 cm

(achievable only with proper optional equipment)

Electronic spacing device C8000:

- 8 programs storable
- control: upto 3 guns with only one program
- alarm when speed is outside the range of minimum/maximum speed set
- data recorded for each gun: total solid line metres
- total data recorded for machine: total driven Km



SPRAYABLE PRODUCTS:

refractive paints, not refractive paints, special paints with antiskid



OPTIONAL EQUIPMENT:

•

- Second automatic paint gun with independent control to stripe 50 cm or 2 lines at the same time (for example continuous line + skip line)

- **Pneumatic support for paint gun (one disc),** to keep automatic gun always at the same distance from ground, ensuring constant width of the line (SUGGESTED OPTIONAL)

- Marking discs, to get a perfect definition of line edges. Useful particularly for concrete surfaces. Available in following widths:

- marking discs for 10-20 cm line

- marking discs for 10-30 cm line

- marking discs for 50 cm line. <u>Attention</u>: 50 cm marking discs can be used only if striper is equipped with optional second automatic paint gun

- Manual paint gun-short with 7 m air hose and 7 m paint hose, for stenciling

- Manual paint gun - long (with extension 40 cm) with 7 m air hose and 7 m paint hose, for stenciling without bending and standing farther from paint spray

- Pressurized glass bead system (SUGGESTED OPTIONAL) consisting of:

- glass bead tank. Available capacity: pressurized conic tank capacity 20 l
 - pressurized tank capacity 26 l

- pressurized conic tank capacity 38,5 l

- automatic glass bead gun with adjustable diffuser
- closing delay regulator for bead gun

- Second automatic glass bead gun with independent delay regulator

<u>Attention</u>: it can be used only if striper is equipped with optional pressurized Glass bead system


- Manual glass bead gun with air hose and bead hose, for bead application on stenciling <u>Attention</u>: it can be used only if striper is equipped with optional pressurized Glass bead system

- Supplementary pressurized tank for paint. Available capacities: - pressurized paint tank capacity 15,5 l - pressurized paint tank capacity 26 l

- 26 I pressurized tank and side extension bracket for pre-marking







L90IETP TECHNICAL DATA SHEET on July 24TH 2017. CMC reserves the right to make changes at any time, without notice.

Macchine Traccialinee Marking Machines