




Tandem-axle trailer VSTP18




VS-mont


 **Trailer length:**
7 150 mm (including drawbar)


 **Trailer width:**
2 550 mm


 **Total load:**
18 000 kg


 **Dead weight:**
from 4 000 kg (depends on tipping body shaping design)


 **Axles:**
BPW / SAF 2 x 9 t, R 22,5"


 **Spring:**
Air spring (mechanic)

 **Tyres:**
385/65 R 22,5" with steel discs

 **Brake system:**
EBS+ 2S/2M WABCO / HALDEX

 **Shaping design:**
S3 - Three-sides tipper:
Loading volume: from 6 m³ (according to customers request)
Length: from 5 000 mm
Hydraulic: Hydraulic cylinder HYVA / PENTA
Used materials: Steel ST 52.3, HARDOX 450, STRENX, sidewalls of aluminium
Used materials: ocel' ST 52.3, HARDOX 450, STRENX, AL PROFIL

 **Shaping design:**
Platform superstructure
Length: from 5 000 mm
Used materials: Steel ST 52.3, HARDOX 450, sidewalls of aluminium

 **Accessories for extra charge:**

- disk brakes
- infocenter - SMARTBOARD
- (counter of driven kilometers, electronic load measuring)
- tarpaulin cover system
- change of material thickness
- change of tipping body shaping design

Lowbed trailer VSP18 / VSP24



Loading space length:
6 500 - 8 000 mm



Trailer length:
9 400 mm (including drawbar)



Total load:
18 000 kg / 24 000 kg



Dead weight:
4 700 kg / 5 700 kg



Axle:
BPW / SAF 2x9 t, 3x9 t, double fitting R 17,5"
1st axle - Fix / Lift axle
2nd axle - Fix axle
3rd axle - Fix axle



Spring:
Air spring - lifting and lowering the trailer



Tyres:
235/75 R 17,5" with steel discs



Brake system:
EBS+ 2S/2M WABCO / HALDEX



Hydraulics:
2x hydraulic cylinder (loading ramps)



Loading bridges:
shiftable towards trailer axis loading inclination angle:
15°, width: 600 mm



Headboard:
detachable



Drawbar height:
950 mm



Equipment:

- support leg height adjustable
- COLAS (adjustable chassis height while loading)



Surcharge version:

- trailer extended version (the width is 3000 mm)
- trailer loading space prolongation
- Infocenter - SMARTBOARD (counter of driven kilometers, electronic load measuring)
- rear ramp in one piece, interconnected in the middle

Turnplate trailer VSPT18 / VSPT24



Trailer length:
7 350 mm / 8 860 mm (including drawbar)



Trailer width:
2 550 mm



Total load:
18 000 kg / 24 000 kg



Dead weight:
od 4 200 kg / 5 200 kg
(depends on tipping body shaping design)



Axles:
BPW / SAF 2x9 t, R 22,5" / 3 x 9 t R 22,5"



Spring:
Air spring (mechanic)



Tyres:
385/65 R 22,5" with steel discs



Brake system:
EBS+ 4S/3M WABCO / HALDEX, including RSS



Shaping design:
S3 - Three-sides tipper:
Loading volume: from 6 m³ (according to customer's request)
Length: from 5 000 mm
Hydraulic: Hydraulic cylinder HYVA / PENTA
Used Materials: Steel ST 52.3, HARDOX 450, DOMEX S 700 MC, AL



Shaping design:
V - platform superstructure
Length: from 5 000 mm
Used materials: Steel ST 52.3, HARDOX 450, sidewalls of aluminium



Accessories for extra charge:

- disk brakes
- infocenter SMARTBOARD (counter of driven kilometers, electronic load measuring)
- tarpaulin cover system
- change of material thickness
- change of tipping body shaping design